

## **Rack-mount KVM Switches**

## **Features**

- \* 1U rack mount design
- \* Up to 16 KVM ports in one unit
- \* 3 layers KVM daisy chain allowed
- \* Plug&Play design, no additional software required
- \* Switch operation: front panel buttons; hot keys under Microsoft Windows; Linux/Unix; Novell
- \* Auto Scan feature with configurable scan interval
- \* Password protection (for OSD models)
- \* PS/2 keyboard and mouse emulation for smooth boot
- \* Supports a variety of mouse device types

## **Specifications**

Model Name		AS-K0004PS	AS-K0008PS-D	AS-K0008DB-D	AS-K0016PS-D	AS-K0016DB-D
Connection						
KVM ports		4	8	8	16	16
Max controlled computers		4	512	512	4096	4096
Interface						
Computer Connection	Keyboard, Mouse	PS/2	PS/2	HDB-15 Female	PS/2	HDB-15 Female
	Monitor	HDB-15 male	HDB-15 male	(combo)	HDB-15 male	(combo)
Console Connection	Keyboard, Mouse	PS/2	PS/2	PS/2	PS/2	PS/2
	Monitor	HDB-15 Female	HDB-15 Female	HDB-15 Female	HDB-15 Female	HDB-15 Female
Cable Type		PS/2 KVM Cable	PS/2 KVM Cable	3-in-1 Cable	PS/2 KVM Cable	3-in-1 Cable
Monitoring and Control						
Port Selection		Hot Key; Button	Hot Key; Button; OSD	Hot Key; Button; OSD	Hot Key; Button; OSD	Hot Key; Button; OSE
Physical and electrical characteristics		5-90sec, step 5sec	5-90sec, step 5sec	5-90sec, step 1sec	5-90sec, step 5sec	5-90sec, step 1sec
Dimensions LxWxH (mm)		131×440×44 (1U)	131×440×44 (1U)	131×440×44 (1U)	125×440×75 (2U)	131×440×44 (1U)

<sup>\*</sup> Specifications are subject to change without notice.